

NEW PRODUCT INFORMATION

2024 NAMM Show 出展のお知らせ

フォスター電機株式会社(フォステクス カンパニー プレジデント:田中英行/
東京都昭島市/以下フォステクスカンパニー)は、2024年1月25日から米国カリ
フォルニア州アナハイムにて開催される、楽器見本市「2024 NAMM Show」にて
下記の新製品を出展いたします。

期間 :2024年1月25日(木)~28日(日)
会場 :米国カリフォルニア州アナハイムコンベンションセンター
HallA Booth 11110

<出展予定の新製品>

プレミアム・ヘッドホン	TH808(展示会初出展)
アクティブスピーカー	PM0.1BD(展示会初出展)
モニタースピーカー	NF06



おかげさまでフォステクスは2023年7月で
創立50周年を迎えました。

Fostex



TH808



NEW

Premium Headphones

TH808

- Equipped with in-house crafted driver units from the TH900 series.
 - Ingenious open housings made of solid black walnut and aluminum
 - High-purity OFC unbalanced cable included
- Type: Open-back Dynamic
Driver: Φ 50mm Neodymium Magnet (1.5 Tesla) / BIODYNA Diaphragm
Weight: Approx.400g (excluding cable)

PM0.3BD

ACTIVE SPEAKER



3.1 kg

- MUSIC / VOICE mode switch to choose sound quality according to the type of source
- Digital (Bluetooth / USB) and analog (AUX) input are supported.
- Newly designed 3inch woofer and 3/4inch soft dome tweeter
- Enclosure structure with separate amplifier section
- Equipped with subwoofer connection terminal
- UL Energy Verified certification for superior energy-saving performance

Enclosure: 2 way bass reflex type

Woofer: 3" Cone woofer

Tweeter: 3/4" soft dome tweeter

Frequency Response: 100Hz - 40kHz

Rated Output Power: 15W + 15W

Dimensions: 110 (W) x 212 (H) x 157 (D) mm

Weight: 3.4 kg (a pair)

NEW

To be launched in the Summer 2024

PM0.1BD

ACTIVE SPEAKER



- Equipped with a newly designed 3inch single-way driver
- Bluetooth and Analog (AUX) input sources are supported
- Enclosure structure with separate amplifier section
- Power-saving mode to reduce power consumption

Enclosure: Bass reflex type

Rated Output Power: 15W + 15W

Dimensions: 110 (W) x 150 (H) x 133 (D) mm

Weight: 2.5 kg (a pair)

Fostex

NEW

To be launched in the Autumn 2024

NF06

MONITOR SPEAKER



Enclosure: 2 way bass reflex type
Woofer: 6.5" HR shaped diaphragm woofer
Tweeter: 1" ridge dome shaped titanium tweeter
Frequency Response: 40Hz - 35kHz
S.P.L.: 84.5dB/W(1m)
Impedance: 8Ω
Crossover Freq.: 1.6kHz -12dB/oct.
Dimensions: 238(W)×400(H)×271(D)mm
Weight: 9.8kg

NF04R

ACTIVE MONITOR SPEAKER

Enclosure type: 2 way bass reflex
Woofer: 4" HR shaped diaphragm woofer
Tweeter: 3/4" soft dome tweeter
Frequency Response: 57Hz - 36kHz
Rated Output Power: Woofer: 30W Tweeter: 20W
Input connector:
XLR-3-31 (balanced), 1/4" TS Phone (unbalanced)
Rated input level:
-10dBV (TS Phone) / +4dBu (XLR) GAIN SW 0dB
-20dBV (TS Phone) / -6dBu (XLR) GAIN SW +10dB
Dimensions: 120 (W) x 189 (H) x 157 (D) mm
Weight: 3.1 kg
Power Consumption: 30W

